



Assembly Instructions

Dog run

Dear customer,

We wish you a lot of enjoyment with your newly ordered product. In the rare case that you are not fully satisfied, please contact us

Phone: 0870 607 34 74
email: enquiries@ideas-4-pets.com
www.ideas-4-pets.com

If you are still experiencing problems you can always contact our **technical helpline** on 07912 270 451 to be helped along.

The run

- Firstly decide where the door panel will go (remember the door is designed to open inwards)
- Each metal panel is four way drilled (two way elongated slot). You simply bolt these together at top and bottom using the M8 bolt and washer sets provided



The roof

The roof slopes from front down towards the back.

- Attach the standard roof supports to the frame of the front panel (The one with the door in it) with even distances between them. They are designed so that they fit over the outer square frame and are then bolted tight. Do not bolt the roof supports very tight to begin with so they are still movable until the roof sheets have been laid on top.
- Secondly, attach the roof support bar to the roof support brackets
- Then attach the roof panels. They need to be laid on top of the roof support, sloping backwards toward the back of the run. We supply special self-tapping screws, which hold these in place. They will “cut themselves” through the roof sheets and into the roof support. There is no need to pre-drill anything. The roof sheets need to be laid over the top of the run, so that they overlap with an overhang at the front of approx 30cm and approx 20cm at the back (total roof overhang is 50cm).

We recommend that all the roof sheets be laid out before attaching to see that there are sufficient roof sheets to make up the roof. You will need then to screw the supplied self-tapping screws through the roof sheets and into the frame of the dog panel. The self-tapping screws need to be screwed through the roof sheets and into the dog run frame with a power drill and an 8 mm tek holder. No pre-drilling required, as the screws supplied are self-tapping.

